

DIN connectors for M&M branded solenoid valves

Coil connectors provide the safest flexible system for connecting M&M International solenoid valves and give a protection class of IP65. They are designed and made of synthetic material offering a high level of electrical insulation. Compliance with UL 1977 and VDE Regulations.

Common Features

Rated voltage (max.): 250 VAC / 300 VDC
 Nominal current: 10 A (Rated) / 16A (max.)
 Wire cross-section: 1.5 mm² (max.)
 Cable entry: PG9 (6 to 8 mm)
 Protection class: IP 65 (only with gasket)
 Insulation class: group C - VDE 0110
 Housing colour: black

Options

Connectors with protection circuits
 Connectors with LED
 Connectors with flying leads
 Other versions available upon request and depending on quantity:
 please contact Rotork Sales Department

Notes

Connectors are supplied with thermoplastic rubber bordered gasket, fixing screw and preinstalled position with ground H 12 (the connector can be spinned when connected)



TYPE: 600 001-



TYPE: 600 011-



Dimensions & weights		600001-	600011-
A	(mm)	28.5	27.7
B	(mm)	14.5	18
C	(mm)	11	18
D	(mm)	21.5	27.7
E	(mm)	41.2	41
F	(mm)	28.8	26.8
G	(mm)	5.5	5.5
weight	(kg)	0.019	0.020

